


6	O-RING	NBR/BUNA-N
5	BUSHING	PTFE
4	STEM	SS410
3	SEAT	NBR, BUNA-N, EPDM
2	DISC	DI, CF8M(SS316), CF8(SS304), WCB, CAST IRON A126
1	BODY	DI, CF8M(SS316), CF8(SS304), WCB, CAST IRON A126

NO.	PARTS NAME	MATERIAL	
TEST PRESSURE	HYDROSTATIC	SHELL	SEAL
		300PSI	220PSI
STANDARD	INSPECTION & TEST	API598	
	END STANDARD	ANSI B16.5 CL150	
	DESIGN	API609	

WAFER NOTCHED TYPE BUTTERFLY VALVE 2" -12"

4E VALVE

UNIT: inch



* PLEASE SPECIFY MATERIAL WHEN PLACING YOUR ORDER.

SIZE	H3	L	ØA	ØE	ØB	ØF	C	ANSI B16.5 CL150	
								ØC	n-Ø
2"	1.181	1.811	0.5	3.543	2.756	0.354	0.394	4.744	4-Ø0.748
2.5"	1.181	1.929	0.5	3.543	2.756	0.354	0.394	5.492	4-Ø0.748
3"	1.181	1.929	0.5	3.543	2.756	0.354	0.394	6.004	4-Ø0.748
4"	1.181	2.165	0.622	3.543	2.756	0.354	0.472	7.5	8-Ø0.748
5"	1.181	2.303	0.75	3.543	2.756	0.354	0.551	8.504	8-Ø0.866
6"	1.181	2.323	0.75	3.543	2.756	0.354	0.551	9.508	8-Ø0.866
8"	1.413	2.52	0.874	4.921	4.016	0.433	0.669	11.752	8-Ø0.866
10"	1.413	2.815	1.126	4.921	4.016	0.433	0.866	14.252	12-Ø0.984
12"	1.413	3.189	1.252	5.906	4.921	0.512	0.945	17.008	12-Ø0.984